

NEW: Telescopic drywall support ST

Provides real support during roof assembly



Simply better.



Flexible in application

It enables the positioning and holding of plaster carton, wooden planks, panels, battens, metal bars, foils and lamp bodies, for example. The support can even be used on sloping roofs:

- due to stable steel pipe construction in three sizes – telescoping up to 2.90 m
- due to 8.5 x 6.5 cm base plates with a swivel range of -45° to +45°

Easy to handle


The support can be used quickly:

- due to the fixing in just two steps: The rough pre-setting is carried out using the telescoping and quickly locking inner pipe; the final clamping is carried out by turning the support at the foam grip

Secure hold

Resilient and anti-slip, the support guarantees secure holding, even on sensitive surfaces:

- due to special steel pipes for a maximum load bearing capacity of up to 60 kg
- due to additional locking of the release button
- due to rubber contact surfaces top and bottom



Telescopic drywall support ST

| Order-No. | Adjusting range mm | Load limit max. kg | kg | qty. | V3 |
|-----------|-----------------------|--------------------------|------|------|----|
| ST125 | 750-1250 | 60 | 1.50 | 10 | |
| ST250 | 1450-2500 | 60 | 2.20 | 10 | |
| ST290 | 1600-2900 | 50 | 2.40 | 10 | |