

# classiX® all-steel bar clamps

Bar clamps for industrial application



Simply better.

## classiX® all-steel bar clamps

The classiX® line of clamps represents an extension of BESSEY®'s clamping and steel manufacturing skills to produce an opening price point offering that also embodies the stringent quality requirements of BESSEY®.

### 1 Choices

A variety of throat depths, pad/swivel styles and clamping capacities provide professionals with a choice that makes sense for real-world applications.

### 2 Quality

Internationally sourced components coordinated by BESSEY® engineering teams to deliver great prices and great quality.

### 3 Standard pads and heavy duty pads

Standard swivel pads and heavy duty pads are tried and true contact surfaces for use with your classiX® clamps. Field replaceable.

### 4 Hardened spindle

Heat-treated, high carbon Acme threaded spindle is manufactured to offer high load capacity, durability and spatter resistance.



	Clamping Capacity	Throat Depth	Clamping Force	Approx. Weight
<b>GS12-8K</b>	4"	3 1/8"	550 lbs	1.00 lbs
<b>GS16K</b>	6"	3 1/8"	550 lbs	1.05 lbs
<b>GS20K</b>	8"	4"	880 lbs	1.90 lbs
<b>GS16-12K</b>	6"	4 3/4"	1000 lbs	2.35 lbs
<b>GS25K</b>	10"	4 3/4"	1000 lbs	2.65 lbs
<b>GS30K</b>	12"	5 1/2"	1200 lbs	3.95 lbs
<b>GS60K</b>	24"	4 3/4"	1200 lbs	5.25 lbs
<b>GSL30</b>	12"	4 3/4"	1880 lbs	5.00 lbs
<b>GSL60</b>	24"	4 3/4"	1880 lbs	6.30 lbs
<b>GSM20</b>	7 1/2"	4 3/4"	2660 lbs	5.20 lbs
<b>GSM25</b>	9"	5 1/2"	2660 lbs	5.75 lbs
<b>GSM30</b>	12"	5 1/2"	2660 lbs	6.35 lbs
<b>GSM40</b>	16"	5 1/2"	2660 lbs	6.70 lbs
<b>GSM50</b>	20"	5 1/2"	2660 lbs	7.40 lbs
<b>GSM60</b>	24"	5 1/2"	2660 lbs	8.10 lbs



GS standard pad



GSL GSM heavy duty pad

